

Batteries and accumulators

TV-

Tauraç

WWW.TAURAC.COM



Introduction

The underground container is rapidly gaining ground among businesses and municipalities due to its highly efficient way of collecting and separating waste. The underground container makes the cityscape more beautiful and cleaner and increases safety.

Difference between the various systems for waste containers

Underground containers are available in different types and sizes. Taurac supplies replacement batteries for underground waste containers that use the technology of BWaste, Mic-O-Data, Sulo, VConsyst and WSS.

In addition, we have the possibility to completely overhaul your existing housing of Mic-O-Data and VConsyst completely overhauled and provided with a new battery.

Battery powered underground waste container

Many underground waste containers use a system. That system can be used for electronic access provision, data registration and communication with battery power. The system provides access control and fill level measurement for (underground) waste containers to which only residents have access by means of a card or key. The system often runs on a battery for a few years. Because the system works on battery power, a connection to the public electrical grid is not necessary.

The flexibility of the access system is determined in part by the battery power. The battery allows the placement of the container without connection to the mains. After some time, the battery will need to be replaced. Taurac offers a wide range of replacement batteries for a BWaste, Mic-O-Data, Sulo, VConsyst and WSS skip. Also systems which keep the batteries in good condition via solar technology are available from Taurac's extensive range!

Advantages of Taurac container batteries

- Same quality as original battery, but in terms of pricing very economical
- Cells in the battery are identical to an original battery
- Dimensions of the housing are identical to an original battery
- Delivery of products from own warehouse
- 1-on-1 personal contact for optimal service

Assortment

Container batteries for underground waste container systems



CON125L 12 Volt / 5200 mAh XX battery suitable for Mic-O-Data system with solarcell



CON10LIPL 10,8 Volt / 43,5Ah lithium battery of Mic-O-Data with lower plate



CON10LI 10,8 Volt / 43,5Ah lithium battery of Mic-O-Data revised



CON1429L

14.4 Volt / 2900 mAh lithium battery suitable for VConsyst Chiplock[®]3.0



CON2472 24 Volt / 72Ah alkaline battery suitable for Sulo



CON1429E

14.4 Volt / 29 Ah lithium battery of VConsyst Chiplock® 4.0 revised



CON1818

18 Volt / 18Ah alkaline battery suitable for BWaste



CON1316

13,5 Volt / 16,5Ah alkaline battery AlkVarta D-cel wired without plug





CON1210 12 Volt / 10Ah lead battery suitable for WSS

CON125L

12 Volt / 5200 mAh lead battery suitable for Mic-O-Data system with solarcell



Specifications

| Reference | Unit | Specificatons |
|--------------------|--------|-----------------------------------|
| Article ID | - | CON125L |
| Voltage | Volt | 12 |
| Amperage | mAh | 5200 |
| Chemistry | - | Lead |
| Suitable for brand | - | Mic-O-Data - art.nr. 90.400.013-1 |
| Warranty | Months | 12 |

CON10LIPL

10,8 Volt / 43,5Ah lithium battery suitable for Mic-O-Data



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|----------------|
| Article ID | - | CON10LIPL |
| Voltage | Volt | 10,8 |
| Amperage | Ah | 43,5 |
| Chemistry | - | Lithium |
| Weight | KG | 1.070 |
| Suitable for brand | - | Mic-o-Data |
| Warranty | Months | 12 |

©2022 Technical data, dimensions and weight are subject to change. Errors and changes reserved.



CON10LIPL

Your current battery for the Mic-O-Data revised. Equipped with a new 10,8 Volt / 43,5Ah lithium battery.

CON1429L

14,4 Volt / 29Ah lithium battery suitable for VConsyst Chiplock[®] 3.0



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|----------------|
| Article ID | - | CON1429L |
| Voltage | Volt | 14,4 |
| Amperage | Ah | 29 |
| Chemistry | - | Lithium |
| Weight | KG | 1.000 |
| Suitable for brand | - | VConsyst |
| Warranty | Months | 12 |
| Certificates | | CE / ISO 9001 |

CON1429E

Your current battery for VConsyst Chiplock[®] 4.0 revised and equipped with 14,4 Volt / 29Ah lithium battery



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|----------------|
| Article ID | - | CON1429L |
| Voltage | Volt | 14,4 |
| Amperage | Ah | 29 |
| Chemistry | - | Lithium |
| Weight | KG | 1.250 |
| Suitable for brand | - | VConsyst |
| Warranty | Months | 12 |
| Certificates | | CE / ISO 9001 |

©2022 Technical data, dimensions and weight are subject to change. Errors and changes reserved.

For the VConsyst 4.0 we can also supply a separate battery pack. The installation of this battery pack can easily be carried out independently. Ask our consultants for more information.

18 Volt / 18Ah alkaline battery suitable for BWaste



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|----------------|
| Article ID | - | CON1818 |
| Voltage | Volt | 18 |
| Amperage | Ah | 18 |
| Chemistry | - | Alkaline |
| Weight | KG | 1.690 |
| Suitable for brand | - | BWaste |
| Warranty | Months | 12 |

24 Volt / 72Ah alkaline battery suitable for Sulo



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|----------------|
| Article ID | - | CON2472 |
| Voltage | Volt | 24 |
| Amperage | Ah | 72 |
| Chemistry | - | Alkaline |
| Weight | KG | 8.960 |
| Dimensions | mm | 250x145x145 |
| Suitable for brand | - | Sulo |
| Garantie | Months | 12 |

12 Volt / 10Ah lead battery suitable for WSS



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|----------------|
| Article ID | - | CON1210 |
| Voltage | Volt | 12 |
| Amperage | Ah | 10 |
| Chemistry | - | Lead |
| Weight | KG | 3.500 |
| Measurements | mm | 152x98x98,4 |
| Connection | - | WSS Connector |
| Brand (original) | - | Sonnenschein |
| Suitable for brand | - | WSS |
| Warranty | Months | 12 |

13,5 Volt / 16,5Ah battery AlkVarta D-cel wired without plug



Specifications

| Reference | Unit | Specifications |
|--------------------|--------|--------------------|
| Article ID | - | CON1316 |
| Voltage | Volt | 13,5 |
| Amperage | Ah | 16,5 |
| Chemistry | - | Alkaline |
| Weight | KG | 1.26 |
| Measurements | mm | 152×98×98,4 |
| Connection | - | Wired without plug |
| Brand (original) | - | Varta |
| Suitable for brand | - | - |
| Warranty | Months | 12 |

Your Taurac dealer in the Benelux: Raca Group B.V.



RACA takes care of it!

As a wholesaler, RACA is a specialist in supplying lighting products, batteries and accumulators. Among other things, RACA supplies LED panels, downlights, highbays, skylights, waterproof fittings, emergency lighting batteries and accumulators. RACA supplies these products to companies operating in various growth sectors such as the installation sector, educational institutions, the medical sector, the construction sector and waste processing. Most of the products are delivered from our own warehouse, which means that fast delivery is possible.

Answering the questions of tomorrow

Years of experience, knowledgeable staff and user-friendly products provide solutions that can answer tomorrow's questions.

Customers appreciate the personal service and solution-oriented way of thinking. All this with the the aim of being able to realize a tailor-made solution for every project.

For more information, please visit www.raca.nl

Your question, RACA takes care of it!

DISCLAIMER

©2022

Technical data and dimensions are subject to possible errors and changes.

All information in this brochure (in any form whatsoever) remains property of Taurac, unless explicitly stated otherwise.

General delivery and sales conditions of the Metaalunie are filed with the Rotterdam Chamber of Commerce and apply to all offers and deliveries.

A copy can be provided on request or look at www.taurac.com



WWW.TAURAC.COM

 \sum info@taurac.com S

(+31)(0)88 500 84 40

Edition 2.1.1