

## Montagehandleiding I1D14601-B

Spot Seoul Dec. Op- & Inbouw plafond plexiglasplaat

+31(0)88 500 84 40

info@taurac.com


www.taurac.com

Scan deze QR code met je telefoon en kom terecht op onze productpagina.



# INSTALLATION INSTRUCTIONS

### LUMINAIRE DIMENSIONS



### Luminaire Specification

Supply voltage	:	230 V
Supply frequency	:	50/60 Hz
Supply current (max)	:	13 mA
Power factor	:	0.65
Total power	:	1.8 W
Charge current (nominal)	:	70 mA
Ambient temperature (ta)	:	0°C-35°C
Protection Class	:	Class II
CCT	:	5500-6000K
Emergency duration	:	3 hours
Recharge period	:	24 hours
IP rating	:	IP20

### Product Features

3 watt NM self-test luminaire with white LED  
 Suitable for surface mount or recessed installation  
 Interchangeable lens-Open Area and Corridor  
 3 Hours duration  
 Integral Test switch  
 Incorporates 4.8V 900mAh Ni-Cd battery pack

### GENERAL DESCRIPTION

A non-maintained emergency luminaire, incorporating an LED module with optional AutoTest. Built in is a deep discharge protection circuit for use with a 4.8V 900 mAh High Temperature NiCd battery pack. Luminaires are provided with interchangeable lenses for use with specific emergency lighting schemes.

### BATTERIES

The luminaire contains a 900mAh rechargeable NiCd battery pack for 3hr operation. Batteries must be replaced when the luminaire can no longer provide 3 hour duration.

### ELECTRICAL INSTALLATION

Luminaires comply with the EMC directive in both mains and emergency operation. The battery lead should be connected only at the time of commissioning. Remove transparent plastic cover to make the relevant electrical connections.

✓ Replace transparent cover to avoid electric shock ✓

### IMPORTANT

Mark the luminaire with the date of commissioning in the space provided on the label.

### FUNCTION TEST

Functional operation of the luminaire can be tested by pressing the test button on the front face of the luminaire. The power LED should illuminate whilst the button is pressed.

### WARRANTY

This product is guaranteed for three years and covers faulty workmanship and materials. The guarantee on the NiMH batteries is 12 months. This Return to Base warranty requires that the product is used within the terms and conditions stated above, in our literature and on our website. Products returned to us under warranty must be carriage paid. Haotian Electronics Ltd. accept no liability for costs incurred.

Suitable for indoor use only.

The LED is non-replaceable and when it reaches its end of life the whole luminaire shall be replaced.